










EMBER STOP MESH - BLACK STAINLESS STEEL

EMBER STOP MESH	<i>Flexi</i>	<i>Tough</i>	<i>Extreme</i>	
				
Roll/Sheet	 Roll	 Roll	 Sheet	 Sheet
Grade	316	316	304	316
Finish	Black Powder Coat	Black Powder Coat	Black Powder Coat	Black Powder Coat
Aperture	1.23 mm	1.67 mm	1.51 mm	1.51 mm
Diameter	0.18 mm	0.45 mm	0.8 mm	0.8 mm
Mesh (openings per lineal inch)	18 x 18	12 x 12	11 x 11	11 x 11
Open Area % *	76 %	62 %	43 %	43 %
BAL 12.5 - FZ 	✓	✓	✓	✓
Formability	Flimsy	Self Supporting	Self Supporting	Self Supporting
Rigidity	Soft	Flexible	Ridgid	Ridgid
Cutting	Scissors	Tin Snips	Guillotine / Grinder	Guillotine / Grinder
Other uses	Insect Mesh	Pet Mesh	Security Mesh	Security Mesh
Dimensions	610 mm x 30 m	190 mm x 30 m	750 mm x 2000 mm	750 mm x 2000 mm
W x L	915 mm x 15 m	915 mm x 15 m	750 mm x 2400 mm	750 mm x 2400 mm
	915 mm x 30 m	915 mm x 30 m	900 mm x 2000 mm	900 mm x 2000 mm
	1220 mm x 15 m	1245 mm x 15 m	900 mm x 2400 mm	900 mm x 2400 mm
	1220 mm x 30 m	1245 mm x 30 m	1200 mm x 2000 mm	1200 mm x 2000 mm
	1550 mm x 15 m	1550 mm x 15 m	1200 mm x 2400 mm	1200 mm x 2400 mm
	1550 mm x 30 m	1550 mm x 30 m	1500 mm x 2000 mm	1500 mm x 2000 mm
	-	-	1500 mm x 2400 mm	1500 mm x 2400 mm

* Pre black powder coat finish



SSWM bushfire mesh can be used to meet the requirements of AS3959-2009 Amdt 3 for BAL 12.5 -FZ, where mesh is referenced and if the prescribed construction requirements are met.



Regular cleaning is recommended to prevent the build-up of contaminants such as dirt and salt.

