
























Product comparison & selection

		 MOST POPULAR			
EXCEEDS AS 3959 	ORDER ONLINE SSWOB 01230	ORDER ONLINE SSWOB 01670 SSWO 01670	SSWOBS 01510	SSWO 01640	
BAL Low - FZ (typically installed)	Low, 12.5	12.5, 19, 29 & 40	40, FZ	40, FZ	
Secondary Application	 Insect Mesh	 Pet Mesh	 Security Mesh	 Industrial Mesh	
PRODUCT SPECIFICATIONS					
Price Indicator	\$	\$\$	\$\$\$	\$\$\$\$	
Roll or Sheet / Cutting					
Finish	● Black (316)	● Black (316) ● Stainless Steel (304/316)	● Black (316)	● Stainless Steel (304/316)	
Formability (handling)	Malleable - SOFT	Self Supporting - FLEXIBLE	Self Supporting - RIGID	Self Supporting - RIGID	
Aperture x Wire Diameter	1.23 x 0.18 mm	1.67 x 0.45 mm	1.51 x 0.80 mm	1.64 x 0.90 mm	
Open Area % <i>Pre black powder coat finish</i>	76 %	62 %	43 %	42%	
QUALITY ASSURED					
	✓ Compliant	✓✓ Tested	✓✓✓ Certified		
AS 3959-2018 Compliant 	✓	✓	✓	✓	
CSIRO FCO-3313 Rev B Independently verified 	✓	✓	✓	✓	
AS/NZS 1530.3:1999 Ignitability 	✓✓	✓✓	✓✓	✓✓	
AS 2331 1.3.1 2001 Neutral Salt Spray Test 		✓✓	✓✓	✓✓	
AS 5041 2003 Knife Shear Test 			✓✓	✓✓	
SHIELD PROTECTION					
USQ Project 1007952 Ember Attack 	✓✓	✓✓✓	✓✓✓	✓✓✓	
AS 1530.8.1 Radiant Heat 		✓✓	✓✓	✓✓	
ASTM E2886 Direct Flame 		✓✓✓	✓✓✓	✓✓✓	
DIMENSIONS W x L					
 Australian Standards: SSWM bushfire mesh can be used to meet the requirements of AS3959-2018 for BAL 12.5 -FZ, where mesh is referenced and if the prescribed construction requirements are met.	610 mm x 30 m	190 mm x 30 m	✓	750 mm x 2000 mm	915 mm x 30 m
	915 mm x 15 m	610 mm x 30 m	✓	750 mm x 2400 mm	1245 mm x 30 m
	915 mm x 30 m	915 mm x 15 m	✓	900 mm x 2000 mm	1550 mm x 30 m
	1220 mm x 15 m	915 mm x 30 m	✓✓	900 mm x 2400 mm	
 Independently Verified: SSWM Bushfire Shield Mesh range has been independently verified by CSIRO and met the physical properties of AS3959-2018. <ul style="list-style-type: none"> ✓ Mesh with max aperture of 2mm ✓ Corrosion resistant steel ✓ Non combustible 	1220 mm x 30 m	1245 mm x 15 m	✓	1200 mm x 2000 mm	
	1550 mm x 15 m	1245 mm x 30 m	✓✓	1200 mm x 2400 mm	
	1550 mm x 30 m	1550 mm x 15 m	✓	1500 mm x 2000 mm	
		1550 mm x 30 m	✓✓	1500 mm x 2400 mm	
		1830 mm x 30 m	✓		