


METRIC	
	Aperture 1.51 mm Wire Diameter 0.8 mm

NEAREST IMPERIAL	
Mesh	11
SWG	21

Stock Status	Stocked
Finish	Black Powder Coat
Weave Type	Plain Weave
Approx Kg/m ² *	3.61 kg/m ²
Approx % Open Area*	43 %

* Pre black powder coat finish

TESTING / STANDARDS	
Mesh is Tested / Manufactured to [^]	
ASTM E2016-15 'Standard Specification for Industrial Woven Wire Cloth'	✓
AS 3959 -2009 Amdt 3 'Construction of Buildings in Bushfire Prone Areas'	✓ Aperture < 2mm Corrosion Resistant Non Combustible
FCO-3313 CSIRO Advisory Report regarding 'Bushfire Mesh' range & criteria of AS 3959-2009	✓ BAL 12.7 - FZ if used in the prescribed construction manner

[^] Refer to the following link for further information
<https://www.sswm.com.au/product/stainless-steel-bushfire-mesh/#testing>

Product Page www.sswm.com.au/product/bushfire-mesh
Care Page www.sswm.com.au/stainless-steel-cleaning-maintenance
Glossary Page www.sswm.com.au/what-is-stainless-steel

PRODUCT CODE	GRADE	 Width mm	 Length mm	APPROX Kg/ SHEET	SHEETS / PACK
SSWOBS 01510 0750 2004	304	750 mm	2000 mm	5.4 Kg	25
SSWOBS 01510 0750 2404	304	750 mm	2400 mm	6.5 Kg	25
SSWOBS 01510 0900 2004	304	900 mm	2000 mm	6.5 Kg	25
SSWOBS 01510 0900 2404	304	900 mm	2400 mm	7.8 Kg	25
SSWOBS 01510 1200 2004	304	1200 mm	2000 mm	8.7 Kg	25
SSWOBS 01510 1200 2404	304	1200 mm	2400 mm	10.4 Kg	25
SSWOBS 01510 1500 2004	304	1500 mm	2000 mm	10.8 Kg	25
SSWOBS 01510 1500 2404	304	1500 mm	2400 mm	13 Kg	25

HEAD OFFICE - Sales & Warehouse 3 Commercial Court, Tullamarine VIC 3043, Australia
t 1300 305 148 f 1300 305 805 Int t +613 9448 9048 Int f +613 8669 4506
sales@sswm.com.au www.sswm.com.au